


# Screw Thread Eye

Lag Thread



No Shoulder  
With Shoulder

Plain = IFST010-----

Plain = ISFST010-----

Galvanized = IFST010-----GD

Galvanized = ISFST010-----GD

Screw Thread Eye Bolt (No Shoulder)						
Diameter (A)	Thread Length (B)	Shank Length (C)	Overall Length (E)	Inside Eye (F)	Outside Eye (G)	Weight per 100
1/4	1 1/2"	1 1/4"	3"	1/2"	1"	5.3
5/16	1 5/8"	1 1/2"	3 1/2"	5/8"	1 1/4"	9
3/8	1 3/4"	1 21/32"	4"	3/4"	1 1/2"	16
1/2	2 1/8"	2 1/16"	5 1/4"	1"	2"	39
5/8	2 1/2"	2 1/2"	6 13/16"	1 1/4"	2 5/16"	67
3/4	3"	2 13/16"	7 1/4"	1 1/2"	2 3/4"	108
7/8	3 1/4"	3 1/4"	8 1/4"	1 3/4"	3 1/2"	166
1	3 1/2"	3 9/16"	9 3/4"	2"	3 3/4"	265

Dimensional specifications per ASME B12.2.1

Screw Thread Eye Bolt (With Shoulder)								
Diameter (A)	Thread Length (B)	Shank Length (C)	Overall Length (E)	Inside Eye (F)	Outside Eye (G)	Weight per 100	Shoulder Thickness (J)	Weight per 100
1/4	1 1/2"	1 1/4"	3"	1/2"	1"	5.3	5/64"	6.7
5/16	1 5/8"	1 1/2"	3 1/2"	5/8"	1 1/4"	9	3/32"	12
3/8	1 3/4"	1 21/32"	4"	3/4"	1 1/2"	16	1/8"	19
1/2	2 1/8"	2 1/16"	5 1/4"	1"	2"	39	5/32"	42
5/8	2 1/2"	2 1/2"	6 13/16"	1 1/4"	2 5/16"	67	13/64"	86
3/4	3"	2 13/16"	7 1/4"	1 1/2"	2 3/4"	108	1/4"	120
7/8	3 1/4"	3 1/4"	8 1/4"	1 3/4"	3 1/2"	166	9/32"	189
1	3 1/2"	3 9/16"	9 3/4"	2"	3 3/4"	265	5/16"	297

